

LST166

Direct Storage Vessel

Lochinvar Ltd
8 Lombard Way
The MXL Centre, Banbury
Oxon, OX16 4TJ

+44 (0) 1295 269981
info@lochinvar.ltd.uk

www.lochinvar.ltd.uk

Key features Include:

- Clean out door
- Enamel lined storage vessel
- 5 year storage vessel warranty

RANGE

Storage Capacity	litres
------------------	--------

EFFICIENCY DATA-Part L2

Standing Loss	kWh/24hrs
---------------	-----------

Insulation Thickness	mm
----------------------	----

Insulation Type	
-----------------	--

EFFICIENCY DATA-ErP and Energy Label

Ecodesign Energy Label rating	
-------------------------------	--

Standing Loss	w
---------------	---

GENERAL DATA

Recovery Rate @ 44°C	l/hr
----------------------	------

Recovery Rate @ 50°C	l/hr
----------------------	------

Recovery Rate @ 56°C	l/hr
----------------------	------

Dimensions (height)	mm
----------------------	----

Dimensions (diameter)	mm
-----------------------	----

Weight (empty)	kg
----------------	----

Weight (full)	kg
---------------	----

Minimum Working Pressure	bar
--------------------------	-----

Maximum Working Pressure	bar
--------------------------	-----

Hot Outlet / Cold Feed Connection (inches)	NPT
--	-----

Flow Connection (inches)	NPT
--------------------------	-----

Return Connection (inches)	NPT
----------------------------	-----

Relief Valve Tapping (inches)	NPT
-------------------------------	-----

Immersion Bosses (inches)	
---------------------------	--

Model

LST166

Storage Capacity	685
------------------	-----

Standing Loss	2.98
---------------	------

Insulation Thickness	75
----------------------	----

Insulation Type	Expanded foam
-----------------	---------------

Ecodesign Energy Label rating	n/a
-------------------------------	-----

Standing Loss	124
---------------	-----

Use heat source data

Use heat source data

Use heat source data

Dimensions (height)	1955
----------------------	------

Dimensions (diameter)	863
-----------------------	-----

Weight (empty)	295
----------------	-----

Weight (full)	980
---------------	-----

Minimum Working Pressure	0.5
--------------------------	-----

Maximum Working Pressure	10.0
--------------------------	------

Hot Outlet / Cold Feed Connection (inches)	2
--	---

Flow Connection (inches)	2½
--------------------------	----

Return Connection (inches)	2½
----------------------------	----

Relief Valve Tapping (inches)	1
-------------------------------	---

Immersion Bosses (inches)	2¼
---------------------------	----

V1 06/2023