

TECHNICAL PRODUCT SUBMITTAL

Squire Indirect water heater



		Model
		SIVT100GE
Storage Capacity	litres	388
EFFICIENCY DATA-Part L2		
Insulation Thickness	mm	70
Insulation Type		Foliflex
Standing Loss	kWh/day	2.4
EFFICIENCY DATA-ErP and Energy Label		
Ecodesign Energy Label rating		C
Standing Loss	W	100
GENERAL DATA		
Max draw off capacity (first hour) at 50°C temperature rise (Top coil only)	l/hr	830
Heat-up Time at 50°C temperature rise (Top coil only)	min	18
Dimensions (height)	mm	1710
Dimensions (diameter)	mm	740
Hot Outlet Connection (inches)	BSP	1½"
Cold Feed Connection (inches)	BSP	1½"
Coil Connection (inches)	BSP	1"
Weight (empty)	kg	145
Weight (full)	kg	533
Minimum Working Pressure	bar	0.5
Maximum Working Pressure	bar	10.0
COIL DATA		
Coil Rating Lower/Upper (80/60°C)	kW	52/37
Coil Surface Area Lower/Upper	m ²	1.64/1.15
Flow Rate Lower/Upper (80/60°C)	l/sec	0.62/0.44
Pressure Loss Lower/Upper	kPa	7.8/3.0
Maximum Coil Temperature	°C	110
Maximum Coil Pressure	bar	16

Squire Indirect water heaters must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of www.lochinvar.ltd.uk

Particular attention should be made to:-

- Dimensions and clearances
- Vented and Unvented installation requirements
- Maintenance

ErP and Warranty

ErP Data including Product Fiche and Energy Labels where applicable and Warranty information are also available at www.lochinvar.ltd.uk

TECHNICAL PRODUCT SUBMITTAL

Squire Indirect water heater

Legend	Description	Unit	SIVT100GE	SIVT110GE	SIVT130GE	SIVT165GE	SIVT220GE
A	Total height	mm	1710	2045	1840	2035	2005
D	Diameter (with insulation)	mm	740	760	910	930	1100
G	Coil outlet (Bottom)	mm	260	260	310	310	350
H	Coil inlet (Bottom)	mm	775	920	910	970	950
J	Coil outlet (Top)	mm	945	1090	1090	1150	1130
K	Coil inlet (Top)	mm	1280	1470	1390	1570	1490
M	Cold water inlet	mm	70	70	85	85	95
N	Hot water outlet	mm	1655	1995	1805	2000	1965
P	Inspection opening	mm	330	330	420	420	450
R	Building return	mm	860	1000	1000	1080	1040
S	Sensor point	mm	500	500	655	655	705
T	T&p connection	mm	1365	1700	1480	1675	1605

Legend	Description	Unit	SIVT100GE	SIVT110GE	SIVT130GE	SIVT165GE	SIVT220GE
1	Cold water inlet connection	BSP Inch	R 1½	R 1½	R 1½	R 1½	R 1½
2	Hot water outlet connection	BSP Inch	R 1½	R 1½	R 1½	R 1½	R 1½
3	Coil outlet	BSP Inch	Rp 1	Rp 1	Rp 1¼	Rp 1¼	Rp 1¼
4	Coil inlet	BSP Inch	Rp 1	Rp 1	Rp 1¼	Rp 1¼	Rp 1¼
5	Building Return	BSP Inch	Rp ¾	Rp ¾	Rp ¾	Rp ¾	Rp ¾
6	Inspection Opening	mm	115	115	180	180	180
7	Connection T&P	BSP Inch	Rp ¾	Rp ¾	Rp ¾	Rp ¾	Rp ¾
8	Sensor point	BSP Inch	Rp ¾	Rp ¾	Rp ¾	Rp ¾	Rp ¾
10	Connection Anode	BSP Inch	Rp 1¼	Rp 1¼	Rp 1¼	Rp 1¼	Rp 1¼

