## **AMICUS LAHP-20HT ERP DATA TABLE**

according regulations 813/2013

Model	LAHP-20HT		
Air to water heat pump	Yes		
Water to water heat pump	No		
Brine to water heat pump	No		
Low temperature heat pump	No		
Equipped with a supplementary heater	No		
Heat pump combination heater	No		
Parameters are declared for medium temperature applications	55°C		
Parameters are declared for average climate conditions			
Item	Symbol	Value	Unit
Rated heat output	P rated	17	[kW]
Tj = -7 [°C]	Pdh	15	[kW]
Tj = 2 [°C]	Pdh	9.12	[kW]
Tj = 7 [°C]	Pdh	5.93	[kW]
Tj = 12 [°C]	Pdh	2.63	[kW]
Tj = -20[°C] operational limit	Pdh	11.72	[kW]
Annual energy consumption	Q <sub>HE</sub>	126.3	GJ
Bivalent temperature	Tbiv	-7	°C
Power consumption in modes other than active	Poff	0.02	[kW]
	Pto	0.02	[kW]
	Psb	0.02	[kW]
	Pck	0	[kW]
Capacity control	Variable		
Sound power level outdoors	Lwa	67	[dB(A)]
Emissions of nitrogen oxides	NOx	0	[mg/kWh]
Item	Symbol	Value	Unit
Seasonal space heating efficiency	ηѕ	134	[%]
Tj = -7 [°C]	COPd	2.26	[-]
Tj = 2 [°C]	COPd	3.37	[-]
Tj = 7 [°C]	COPd	4.29	[-]
Tj = 12 [°C]	COPd	5.58	[-]
Tj = -7 [°C]	COPd	2.26	[-]
Tj = -10 [°C]	COPd	2.05	[-]
Operating limit temperature	TOL	-16	[°C]
Cycling interval efficiency	COPcyc	4.28	[-]
Heating water operational limit	WTOL	65	[°C]
Supplementary heater rated output	Monovalent		
Rated airflow outdoors		7030	[m³/h]

according commission delegated regulation (EU) No 813/2013

ErP data table\_LAHP-20HT\_february2016

