

AMICUS LAHP-602HT ERP DATA TABLE

according regulations 813/2013

Model	LAHP-602HT		
Air to water heat pump	Yes		
Water to water heat pump	No		
Brine to water heat pump	No		
Low temperature heat pump	No		
Equipped with a supplementary heater	No		
Heat pump combination heater	No		
Parameters are declared for medium temperature applications	55°C		
Parameters are declared for average climate conditions			
Item	Symbol	Value	Unit
Rated heat output	P rated	46.9	[kW]
T _j = -7 [°C]	P _{dh}	41.5	[kW]
T _j = 2 [°C]	P _{dh}	25.3	[kW]
T _j = 7 [°C]	P _{dh}	16.3	[kW]
T _j = 12 [°C]	P _{dh}	7.24	[kW]
Annual energy consumption	Q _{HE}	348	GJ
Bivalent temperature	T _{biv}	-7	°C
Power consumption in modes other than active	P _{off}	0.02	[kW]
	P _{to}	0.02	[kW]
	P _{sb}	0.02	[kW]
	P _{ck}	0.186	[kW]
Capacity control	Variable		
Sound power level outdoors	L _{wa}	74	[dB(A)]
Emissions of nitrogen oxides	NO _x	0	[mg/kWh]
Item	Symbol	Value	Unit
Seasonal space heating efficiency	η _s	116	[%]
T _j = -7 [°C]	COP _d	1.88	[-]
T _j = 2 [°C]	COP _d	2.98	[-]
T _j = 7 [°C]	COP _d	3.88	[-]
T _j = 12 [°C]	COP _d	4.48	[-]
T _j = -7 [°C]	COP _d	1.88	[-]
T _j = -10 [°C]	COP _d	1.67	[-]
Operating limit temperature	TOL	-20	[°C]
Heating water operational limit	WTOL	65	[°C]
Supplementary heater rated output	Monovalent		
Rated airflow outdoors		29348	[m ³ /h]

1. according commission delegated regulation (EU) No 813/2013

ErP data table_LAHP-602HT_february2016

