

AMICUS LAHP-1002LT PRODUCT FICHE

According regulations 811/2013 and 812/2013

Model		LAHP1002LT	
Energy class	A++		
Air-to-water heat pump	Yes		
Low-temperature heat pump	Yes		
Supplementary heater	No		
Heat pump combination heater	No		
Item	Symbol	Value	Units of measurement
Rated heat output	Prated	68.19	[kW]
Tj = -7 [°C]	Pdh	60.32	[kW]
Tj = 2 [°C]	Pdh	44.33	[kW]
Tj = 7 [°C]	Pdh	53.52	[kW]
Tj = 12 [°C]	Pdh	60.99	[kW]
Tj = -7 [°C]	Pdh	60.32	[kW]
Tj = -9 [°C]	Pdh	56.13	[kW]
Tbivalent	Tbiv	-7	[°C]
Cycling interval capacity for heating	Pcych	-	[kW]
Degradation coefficient	Cdh	0.9295	[-]
Power consumption in off mode	Poff	0.02	[kW]
Power consumption in thermostat-off mode	Pto	0.3999	[kW]
Power consumption in standby mode	Psb	0.02	[kW]
Power consumption in crankcase heater mode	Pck	0.2	[kW]
Capacity control		Step	
Sound power level, indoor/outdoor measured	Lwa	0/83	[dB(A)]
Emissions of nitrogen oxides	NOx	0	[mg/kWh]
Seasonal space heating energy efficiency	ηs	150.800	[%]
Tj = -7 [°C]	COPd	2.414	[-]
Tj = 2 [°C]	COPd	3.789	[-]
Tj = 7 [°C]	COPd	5.686	[-]
Tj = 12 [°C]	COPd	7.204	[-]
Tj = -7 [°C]	COPd	2.414	[-]
Tj = -9 [°C]	COPd	2.219	[-]
Operation limit temperature	TOL	-16	[°C]
Cycling interval efficiency	COPcyc	-	[-]
Heating water operating limit temperature	WTOL	60	[°C]
Air flow rate		36998	[m ³ /h]
Heating energy demand		95664	[kWh]
Total electrical consumption		24880	[kWh]
SCOP		3.845	[-]
Climatic condition		Average	

ErP product fiche_LAHP-1002LT_September 2019

