

AMICUS LAHP-4004LT PRODUCT FICHE

According regulations 811/2013 and 812/2013

Model		LAHP-4004LT	
Energy class	N/A		
Air-to-water heat pump	Yes		
Low-temperature heat pump	Yes		
Supplementary heater	No		
Heat pump combination heater	No		
Item	Symbol	Value	Units of measurement
Rated heat output	Prated	240.7	[kW]
Tj = -7 [°C]	Pdh	212.9	[kW]
Tj = 2 [°C]	Pdh	129.6	[kW]
Tj = 7 [°C]	Pdh	110.2	[kW]
Tj = 12 [°C]	Pdh	124.6	[kW]
Tj = -7 [°C]	Pdh	212.9	[kW]
Tj = -9 [°C]	Pdh	197.8	[kW]
Tbivalent	Tbiv	-7	[°C]
Cycling interval capacity for heating	Pcych	-	[kW]
Degradation coefficient	Cdh	0.9173	[-]
Power consumption in off mode	Poff	0.02	[kW]
Power consumption in thermostat-off mode	Pto	1.124	[kW]
Power consumption in standby mode	Psb	0.02	[kW]
Power consumption in crankcase heater mode	Pck	0.4	[kW]
Capacity control		Step	
Sound power level, indoor/outdoor measured	Lwa	0/90	[dB(A)]
Emissions of nitrogen oxides	NOx	0	[mg/kWh]
Seasonal space heating energy efficiency	ηs	152.400	[%]
Tj = -7 [°C]	COPd	2.411	[-]
Tj = 2 [°C]	COPd	3.759	[-]
Tj = 7 [°C]	COPd	5.506	[-]
Tj = 12 [°C]	COPd	6.801	[-]
Tj = -7 [°C]	COPd	2.411	[-]
Tj = -9 [°C]	COPd	2.196	[-]
Operation limit temperature	TOL	-16	[°C]
Cycling interval efficiency	COPcyc	-	[-]
Heating water operating limit temperature	WTOL	60	[°C]
Air flow rate		116904	[m ³ /h]
Heating energy demand		338115	[kWh]
Total electrical consumption		87031	[kWh]
SCOP		3.885	[-]
Climatic condition		Average	

ErP product fiche_LAHP-4004LT_September 2019

