

Lochinvar Ltd 8 Lombard Way The MXL Centre, Banbury Oxon, OX16 4TJ


+44 (0) 1295 269981 info@lochinvar.ltd.uk www.lochinvar.ltd.uk

Technical details

DRIVE	
Pump Type	
Motor	
Electrical Requirements	
Enclosure Rating	
Thermal Class	
Temperature class	
Bearings	
Operating Modes	
GENERAL DATA	
Pump Housing	
Impellor	
Connection Type	
Connection Size	inch
Maximum Pressure	bar
Liquid Temperature Range	°C
Weight	kg
Min-Maximum Power consumption	W
Min-Maximum Current draw	Α
Approvals	
DIMENSIONS	
Port to port length	mm

aximum Current draw	Α
<i>r</i> als	
ISIONS	
port length	mm
402 402 048	133 133

Potable Water	
Electric with inte	egrated motor protection
230V /1Ph/ 50h:	z
IP55	
F	
TF120	
Product lubricat	ed special plain bearing
Integrated frequ	iency converter
Stainless Steel	
Composite	
DIN PN 6/10	
DN65	
10	
-10 / 110°C	
24.6	
16-763	
0.18-3.45	
CE,WEEE,WRAS	
340	
	La





















Lochinvar Ltd 8 Lombard Way The MXL Centre, Banbury Oxon, OX16 4TJ

+44 (0) 1295 269981 info@lochinvar.ltd.uk www.lochinvar.ltd.uk

Pump curve **97924365**

