

# TECHNICAL PRODUCT SUBMITTAL

## TTB580



Nominal Input (gross)	kW	611
Gas Flow Rate (natural gas)	m <sup>3</sup> /hr	58.2
Output @50/30°C	kW	576
Output @55/35°C	kW	569
Output @80/60°C	kW	535
<b>EFFICIENCY DATA-Part L2</b>		
Seasonal Efficiency (@80/60°C According to EN15502)	%	95.6
Seasonal Efficiency (@55/35°C According to EN15502)	%	97.1
<b>EFFICIENCY DATA-ErP and Energy Label</b>		
Ecodesign Energy Label rating		n/a
Seasonal space heating energy efficiency	%	n/a
<b>GENERAL DATA</b>		
NOx emission @0% O <sub>2</sub>	mg/kWh	41
Dimensions (height )	mm	1638
Dimensions (width)	mm	736
Dimensions (depth)	mm	1094
Water Content	litres	43
Weight (empty)	kg	450
Weight (full)	kg	493
Flow Connection (inches)	BSP	R2½
Return Connection (inches)	BSP	R2½
Gas Connection (inches)	BSP	R2
Electrical Requirements		230V /1Ph/ 50hz
Power Consumption	W	960
Sound Power Level	LWA(db)	78
Maximum Flue Gas Temperature	°C	90
Max Flow Temperature	°C	85
Minimum Working Pressure	bar	1.0
Maximum Working Pressure	bar	4.0

**TTB boilers** must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of [www.lochinvar.ltd.uk](http://www.lochinvar.ltd.uk)

Particular attention should be made to:-


- Dimensions and clearances
- Vented and Unvented installation requirements
- maintenance

### **ErP and Warranty**

ErP Data including Product Fiche and Energy Labels where applicable and Warranty information are also available at [www.lochinvar.ltd.uk](http://www.lochinvar.ltd.uk)

# TECHNICAL PRODUCT SUBMITTAL

## TTB580



Item	Description	Unit	TTB410	TTB580
			Size	Size
A	water flow (outlet)	Inch	2½"	2½"
B	water return (inlet)	Inch	2½"	2½"
C	cable input	mm	Ø 22,5	Ø 22,5
D	combustion air inlet	mm	180	180
E	flue terminal	mm	180	180
F	gas connection	Inch	2"	2"
G	condensate discharge hose	mm	Ø 25	Ø 25