

TECHNICAL PRODUCT SUBMITTAL

AMICUS LAHP-702LT AIR SOURCE HEAT PUMP

EFFICIENCY DATA -Part L2		
Heating Capacity (EN14511) external air+7C 30/35 flow	kW	67.3
Total Power input (EN14511) external air+7C 30/35 flow	kW	15.1
COP (EN14511) external air+7C 30/35 flow	W/W	4.46
EFFICIENCY DATA -ErP and Energy Label		
Energy Label Rating Low temperature		A++
SCOP Low Temperature		4.04
Seasonal Efficiency Low temperature	%	158.4
GENERAL		
Refrigerant type		R410A
Compressor Type		Scroll
Number of Compressors		2
Number of Circuits		1
Capacity steps		2
Minimum capacity step	%	50
ELECTRICAL DATA		
Power supply	V/Ph/Hz	400/3+N/50
Maximum input power	kW	31
Maximum input current standard unit	A (per phase)	54
Peak input current standard unit	A (per phase)	147
Peak input current unit with soft start option fitted	A (per phase)	100
Fuse rating (delayed)	A	125
Optional Hydraulic kit input power	kW	1.1
Optional Hydraulic kit maximum input current	A	2.45
FANS		
Fan type (standard unit)		Axial
Number of fans (standard unit)		2
Air flow rate for design	m ³ /h	19800
Sound power level ²	dB(A)	77
Sound pressure level ³	dB(A)	45
WATER		
Flow/Return connections	inch	2"
Nominal flow rate	L/sec	4.28
Pressure drop across the heat exchanger	kPa	54
Minimum water content in the user circuit	litre	750
BREEAM DATA		
Total refrigerant charge	kg	14.9
Operational life	Years	20
Global warming potential		2088

TECHNICAL PRODUCT SUBMITTAL

AMICUS LAHP-702LT AIR SOURCE HEAT PUMP

LAHP-702LT			Heating OUT						
Water Delivery Temperature			35C	40C	45C	50C	55C	59C	Max outlet
performance data	-10	Heat Output (KW)	35.5	34.5	33.4	N/A	N/A	N/A	45c
		Efficiency COP	2.3	2.0	1.8	N/A	N/A	N/A	
	-7	Heat Output (KW)	39.1	37.8	36.6	35.2	N/A	N/A	50c
		Efficiency COP	2.5	2.2	1.9	1.6	N/A	N/A	
	-5	Heat Output (KW)	41.3	40.0	38.7	37.3	N/A	N/A	50c
		Efficiency COP	2.7	2.3	2.0	1.7	N/A	N/A	
	-4	Heat Output (KW)	42.5	41.2	39.8	38.8	N/A	N/A	50c
		Efficiency COP	2.8	2.4	2.1	1.8	N/A	N/A	
	-3	Heat Output (KW)	43.7	42.7	41.7	41.2	N/A	N/A	50c
		Efficiency COP	2.8	2.5	2.18	1.9	N/A	N/A	
	-2	Heat Output (KW)	45.7	44.9	43.9	43.3	N/A	N/A	50c
		Efficiency COP	3.0	2.6	2.3	2.0	N/A	N/A	
	0	Heat Output (KW)	50.6	49.4	48.7	47.8	47.1	N/A	55c
		Efficiency COP	3.3	2.9	2.6	2.2	2.0	N/A	
	5	Heat Output (KW)	62.4	61.6	60.5	59.8	59.0	N/A	55c
		Efficiency COP	4.1	3.6	3.2	2.8	2.5	N/A	
	10	Heat Output (KW)	72.9	71.3	69.9	68.3	66.7	N/A	55c
		Efficiency COP	4.9	4.3	3.8	3.3	2.9	N/A	
15	Heat Output (KW)	80.8	79.1	77.2	75.5	73.4	72.3	59c	
	Efficiency COP	5.5	4.9	4.2	3.7	3.2	2.85		
20	Heat Output (KW)	89.5	87.2	85.0	82.7	80.5	79	59c	
	Efficiency COP	6.1	5.4	4.7	4.1	3.5	3.11		

Optional Hydraulic kit Pump details			
Model			LAHP702LT
Nominal Input power		kW	1.1
Nominal Input current		A	2.45
Nominal water flow rate		l/h	11780
Total head available at the pump		kPa	182
Available head for system pipework		kPa	126
Power supply		V/ph/Hz	400/3/50

Amicus air to water heat pumps must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of www.lochinvar.ltd.uk