

## EcoSword gas fired condensing water heaters

### Key features Include:

- On board controls
- Enamel lined storage vessel
- Factory fitted Correx

		<b>Model</b>
		<b>LGC 160-350 CE</b>
Nominal Input (net)	kW	18.2
Nominal Input (gross)	kW	20.0
Gas Flow Rate (natural gas)	m <sup>3</sup> /hr	1.9
Nominal Output	kW	19.1
<b>EFFICIENCY DATA-Building Regulations</b>		
Seasonal Efficiency (Part L2 Gross CV)	%	95.5
Maintenance Consumption value	MJ/M	236.5
<b>EFFICIENCY DATA-ErP and Energy Label</b>		
Ecodesign Energy Label rating		A
Water Heater efficiency	%	92
<b>GENERAL DATA</b>		
NOx emission @0% O <sub>2</sub>	mg/kWh	30
Recovery Rate @ 44°C	l/hr	375
Recovery Rate @ 50°C	l/hr	330
Recovery Rate @ 56°C	l/hr	295
Dimensions (height )	mm	1269
Dimensions (diameter)	mm	560
Dimensions (depth)	mm	760
Storage Capacity	litres	163
Weight (empty)	kg	95
Weight (full)	kg	258
Insulation Thickness	mm	50
Insulation Material		Polyurethane
Hot Outlet Connection (inches)	BSP (Female)	¾"
Cold Feed Connection (inches)	BSP (Female)	¾"
Gas Connection (mm)	CU (Male)	15
Condense Connection (mm)	OD (Female)	40
Electrical Requirements		230V /1Ph/ 50hz
Power Consumption	W	85
Sound Power Level	LWA(db)	52
Maximum Flue Gas Temperature	°C	61
Max Outlet Temperature	°C	85
Maximum Working Pressure	bar	8

**EcoSword water heaters** must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of [www.lochinvar.ltd.uk](http://www.lochinvar.ltd.uk)

Particular attention should be made to:-

- Dimensions and clearances page 38/80
- Vented and Unvented installation requirements page 39/40
- maintenance page 61

### ErP and Warranty

ErP Data including Product Fiche and Energy Labels where applicable and Warranty information are also available at [www.lochinvar.ltd.uk](http://www.lochinvar.ltd.uk)