

TECHNICAL PRODUCT SUBMITTAL

AMICUS LAHP-242HTS STANDARD AIR SOURCE HEAT PUMP

Data	Unit	Model
		LAHP-242HTS
Heating Data		
Heating Capacity (EN14511) ¹	kW	23.8
Total Power input (EN14511) ¹	kW	5.31
COP (EN14511) ¹	W/W	4.48
Nominal flow rate	m ³ /h	4.16
Pressure drop across the heat pump	kPa	35.7
Design air flow rate	m ³ /h	8384
EcoDesign data ²		
Energy Label Rating Low temperature		A++
SCOP Low Temperature		3.95
Seasonal Efficiency Low temperature	%	155
Energy Label Rating High temperature		A++
SCOP High Temperature		3.17
Seasonal Efficiency High temperature	%	124
Cooling Data		
Cooling Capacity (EN14511) ³	kW	22.8
Total Power input (EN14511) ³	kW	7.07
EER (EN14511) ³	W/W	3.22
Nominal flow rate	m ³ /h	3.86
Pressure drop across the heat pump	kPa	24.9
Design air flow rate	m ³ /h	8924
General data		
Refrigerant		R410A
Compressor Type		E.V.I. Scroll
Number of Compressors		2
Number of Circuits		1
Capacity steps		2
Minimum capacity step	%	50
Sound power level	dB(A)	82
Sound pressure level (10m)	dB(A)	50
Minimum water content in the user circuit	litre	250
Electrical Data		
Power supply	V/Ph/Hz	400/3+N/50
Maximum input power	kW	11.8
Maximum input current standard unit	A	21.8
Peak input current standard unit	A	64.1
Peak input current unit with soft start option fitted	A	43
Fuse rating (delayed)	A	32
Fans		
Type		Axial EC
Number of fans (standard unit)	n ^o	1

TECHNICAL PRODUCT SUBMITTAL



AMICUS LAHP-242HTS STANDARD AIR SOURCE HEAT PUMP

LAHP-242HTS		Heating OUT							Max Outlet	
Water Delivery Temperature		35C	40C	45C	50C	55C	60C	63C		
Source air temperature	-10	Heat Output (KW)	13.5	13.6	13.6	13.7	13.7	N/A	N/A	55°C
		Efficiency COP	2.6	2.3	2.1	1.9	1.7	N/A	N/A	
	-8	Heat Output (KW)	14.3	14.3	14.3	14.4	14.5	N/A	N/A	55°C
		Efficiency COP	2.7	2.5	2.2	2.0	1.8	N/A	N/A	
	-6	Heat Output (KW)	14.9	15.0	15.0	15.0	15.1	15.2	N/A	60°C
		Efficiency COP	2.8	2.6	2.3	2.1	1.9	1.7	N/A	
	-4	Heat Output (KW)	15.6	15.6	15.7	15.7	15.7	15.7	N/A	60°C
		Efficiency COP	2.9	2.7	2.4	2.2	1.9	1.7	N/A	
	-2	Heat Output (KW)	16.7	16.8	16.9	16.9	17.0	17.3	17.3	63°C
		Efficiency COP	3.1	2.8	2.6	2.3	2.1	1.9	1.8	
	0	Heat Output (KW)	18.2	18.3	18.4	18.5	18.6	18.8	18.9	63°C
		Efficiency COP	3.4	3.1	2.8	2.5	2.3	2.0	1.9	
	2	Heat Output (KW)	19.6	19.7	19.9	20.0	20.2	20.4	20.5	63°C
		Efficiency COP	3.6	3.3	3.0	2.7	2.4	2.2	2.1	
	4	Heat Output (KW)	21.2	21.3	21.5	21.7	21.9	22.2	22.3	63°C
		Efficiency COP	3.9	3.5	3.2	2.9	2.6	2.4	2.2	
	6	Heat Output (KW)	22.9	23.0	23.2	23.4	23.6	23.9	24.1	63°C
		Efficiency COP	4.2	3.8	3.4	3.1	2.8	2.5	2.4	
	7	Heat Output (KW)	23.7	23.7	23.8	24.0	24.2	24.4	24.5	63°C
		Efficiency COP	4.4	3.9	3.5	3.2	2.9	2.6	2.4	
8	Heat Output (KW)	24.2	24.2	24.3	24.4	24.6	24.8	24.9	63°C	
	Efficiency COP	4.4	4.0	3.6	3.2	2.9	2.6	2.5		
10	Heat Output (KW)	25.3	25.3	25.3	25.4	25.5	25.7	25.8	63°C	
	Efficiency COP	4.6	4.2	3.7	3.3	3.0	2.7	2.6		
15	Heat Output (KW)	28.3	28.2	28.0	27.9	27.9	27.9	28.0	63°C	
	Efficiency COP	5.2	4.6	4.1	3.7	3.3	2.9	2.8		
20	Heat Output (KW)	31.8	31.4	31.1	30.8	30.6	30.5	30.4	63°C	
	Efficiency COP	5.9	5.2	4.6	4.0	3.6	3.2	3.0		
25	Heat Output (KW)	35.6	34.7	34.1	33.5	33.0	32.7	32.5	63°C	
	Efficiency COP	6.8	5.8	5.1	4.4	3.9	3.4	3.2		

Amicus air to water heat pumps must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of www.lochinvar.ltd.uk




TECHNICAL PRODUCT SUBMITTAL

AMICUS LAHP-242HTS STANDARD AIR SOURCE HEAT PUMP


model	octave bands (hz)								lw		lp
	63	125	250	500	1k	2k	4k	8k	db	db	db
	db	db	db	db	db	db	db	db			
252HTS	91.1	82.3	76.2	74.7	73.6	68.2	64.8	55.7	91.9	82	50
302HTS	91.1	82.3	76.2	74.7	73.6	68.2	64.8	55.7	91.9	83	51
432HTS	92.1	83.3	77.2	75.7	74.6	69.2	65.8	56.7	92.9	84	52
492HTS	93.1	84.3	79.2	76.7	75.6	70.2	66.8	57.7	93.9	84	52
602HTS	93.1	84.3	79.2	76.7	75.6	70.2	66.8	57.7	93.9	83	51
752HTS	93.1	84.3	79.2	76.7	75.6	70.2	66.8	57.7	93.9	84	52
852HTS	93.1	84.3	79.2	76.7	75.6	70.2	66.8	57.7	93.9	84	52
1002HTS	93.1	84.3	79.2	76.7	75.6	70.2	66.8	57.7	93.9	84	52
1202HTS	93.1	84.3	79.2	76.7	75.6	70.2	66.8	57.7	93.9	87	55
1454HTS	100.1	91.3	85.2	83.7	82.6	77.2	73.8	64.7	100.9	88	56
1654HTS	100.1	91.3	85.2	83.7	82.6	77.2	73.8	64.7	100.9	89	57
1854HTS	101.1	92.3	86.2	84.7	83.6	78.2	74.8	65.7	101.9	88	56
2154HTS	102.1	93.3	87.2	85.7	84.6	79.2	75.8	66.7	102.9	89	57

TECHNICAL PRODUCT SUBMITTAL

AMICUS LAHP-242HTS STANDARD AIR SOURCE HEAT PUMP



SEZIONE A-A



	242, 202 84E L.S.	242, 202 146E L.S.
Rp		
Ep	PANNELLO ASPORTABILE - REMOVABLE PANEL	
Ea	QUADRO ELETTRICO - ELECTRICAL PANEL	
Ca	INGRESSO ALIMENTAZIONE ELETTRICA - POWER SUPPLY INLET	
IN UT	SCARICO CONDENSA - CONDENSATE DRAIN	Ø 1" GAS F
OUT REC	INGRESSO ACQUA UTENTE - USER WATER INLET	Ø 1" 1/4 GAS M
IN REC	USCITA ACQUA UTENTE - USER WATER OUTLET	Ø 1" 1/4 GAS M
OUT REC	INGRESSO ACQUA RECUPERO - RECOVERY WATER INLET	Ø 1" 1/4 GAS M
	USCITA ACQUA RECUPERO - RECOVERY WATER OUTLET	Ø 1" 1/4 GAS M