TECHNICAL PRODUCT SUBMITTAL



LOK Packaged Plate Heat Exchangers

Key features Include:

- High Efficiency
- 316 Stainless Steel vessel
- WRAS Approved

Output	
Heat Transfer Duty	kW
Thermal efficiency	%
Primary Side	
Inlet Temperature	°C
Outlet Temperature	°C
Fluid Flow Rate	litre/second
Fluid type	
Connection size and type	
Max Working Temperature	°C
Maximum Working Pressure	bar
Secondary Side	
Inlet Temperature	°C
Outlet Temperature	°C
Fluid Flow Rate	litres/second
Fluid type	
pressure drop	bar
Connection size and type	Inch BSPT Male
Max Working Temperature	°C
Maximum Working Pressure	bar
Performance	
Recovery Rate @ 55°C ∆T	litres/hour
Recovery Rate @ 55°C ∆T	litres/second
Recovery Rate @ 50°C ∆T	litres/hour
Recovery Rate @ 50°C ∆T	litres/second
Dimensions	
Height	mm
Width	mm
Depth	mm
Construction Details	
Number Of Plates	
Plate Material	
Gasket Material	
Empty weight single head primary pump	kg
Empty weight twin head primary pump	kg
WRAS Approval Number	

Model	
LOK14-4	50

LOK14-450	
450	
99.5	
82	
Varies Depending On Demand (49 At Full Demand)	
3.33	
Water	
DN40 PN6 Flange	
99	
6	
Varies Depending On Demand (10 At Full Demand)	
65	
1.97	
water	
0.16	
2"	
85	
6	
7092.0	
1.97	
7812	
2.17	
1541	
643	
964	
25	
AISI 316 Stainless Steel	
EPDM - Clip On	
189	
210	
1401052	

LOK packaged plate heat exchangers must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of www.lochinvar.ltd.uk