

TECHNICAL PRODUCT SUBMITTAL

LOKT8-150



Heat Transfer Duty	kW	150
Thermal efficiency	%	99.5
Primary Side		
Inlet Temperature	°C	82
Outlet Temperature	°C	Varies Depending On Demand (50 At Full Demand)
Fluid Flow Rate	litre/second	1.14
Fluid type		Water
Connection size and type	Inch BSPT Female	1 1/4
Max Working Temperature	°C	99
Maximum Working Pressure	bar	10
Secondary Side		
Inlet Temperature	°C	Varies Depending On Demand (10 At Full Demand)
Outlet Temperature	°C	65
Fluid Flow Rate	litres/second	0.66
Fluid type		water
pressure drop	bar	0.15
Connection size and type	Inch BSPT Male	1 1/4
Max Working Temperature	°C	85
Maximum Working Pressure	bar	10
Performance		
Recovery Rate @ 55°C ΔT	litres/hour	2376
Recovery Rate @ 55°C ΔT	litres/second	0.66
Recovery Rate @ 50°C ΔT	litres/hour	2628
Recovery Rate @ 50°C ΔT	litres/second	0.73
Dimensions		
Height	mm	1445
Width	mm	643
Depth	mm	1023
Construction Details		
Number Of Plates		22
Plate Material		AISI 316 Stainless Steel
Gasket Material		EPDM - Clip On
Empty weight single head primary pump	kg	116
Empty weight twin head primary pump	kg	135
WRAS Approval Number		1401052

LOK packaged plate heat exchangers must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of www.lochinvar.ltd.uk

Particular attention should be made to:-

- Dimensions and clearances
- Vented and Unvented installation requirements
- maintenance

Warranty

Warranty information are also available at www.lochinvar.ltd.uk

TECHNICAL PRODUCT SUBMITTAL

LOKT8-150

