

TECHNICAL PRODUCT SUBMITTAL



SST Direct Storage vessel

Key features Include:

- Clean out door
- Stainless steel storage vessel
- 10 year storage vessel warranty

RANGE

Storage Capacity	litres
------------------	--------

EFFICIENCY DATA-Part L2

Insulation Thickness	mm
----------------------	----

Insulation Type	
-----------------	--

EFFICIENCY DATA-ErP and Energy Label

Ecodesign Energy Label rating	
-------------------------------	--

Standing Loss	W
---------------	---

GENERAL DATA

Recovery Rate @ 44°C	l/hr
----------------------	------

Recovery Rate @ 50°C	l/hr
----------------------	------

Recovery Rate @ 56°C	l/hr
----------------------	------

Dimensions (height)	mm
----------------------	----

Dimensions (diameter)	mm
-----------------------	----

Weight (empty)	kg
----------------	----

Weight (full)	kg
---------------	----

Minimum Working Pressure	bar
--------------------------	-----

Maximum Working Pressure	bar
--------------------------	-----

Model

SST220

1000

50

Polyurethane

N/A

143

Use heat source data

Use heat source data

Use heat source data

1907

1080

175

1175

0.5

6

SST Direct storage vessels must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of www.lochinvar.ltd.uk

If the SST Direct storage vessel is being used alongside a gas fired water heater then the Installation Commissioning and Maintenance instructions for the gas appliance should also be consulted prior to installation as the installation requirements may differ.

Particular attention should be made to:-

- Dimensions and clearances page 5
- Vented and Unvented installation requirements page 7
- Maintenance page 13

ErP and Warranty

ErP Data including Product Fiche and Energy Labels where applicable and Warranty information are also available at www.lochinvar.ltd.uk