

TECHNICAL PRODUCT SUBMITTAL



Range

LBF high efficiency gas fired Water Heaters

Nominal Input (net) – kW	29.0
Nominal Input (gross) – kW	32.2
Gas Flow Rate (natural gas) – m ³ /hr	2.99
Nominal Output – kW	26.6
Efficiency (Part L2 Gross CV) – %	82.7
NO _x Emissions (corrected to 0% O ₂) – ppm	128
NO _x Emissions (corrected to 0% O ₂) – mg/kWh	225
Recovery Rate @ 44°C Δt – l/hr	520
Recovery Rate @ 50°C Δt – l/hr	458
Recovery Rate @ 56°C Δt – l/hr	409
Dimensions (height) – mm	2275
Dimensions (width) – mm	720
Dimensions (depth) – mm	720
Storage Capacity – litres	390
Weight (empty) – kgs	309
Weight (full) – kgs	699
Water Connection – inches BSP Rp (Internal parallel)	1¼
Gas Connection – inches BSP Rp (Internal parallel)	½
Flue Diameter (concentric) – mm	60/100
Flue Diameter (twin-pipe) – mm	80/80
Electrical Requirements	230v 1ph 50Hz
Power Consumption – W	67
CO ₂ Flue Gas - %	6.4
Maximum Flue Gas Temperature - °C	97
Max Outlet Temperature - °C	74
Max Working Pressure – bar	6.0

Lochinvar **LBF** series high efficiency floor standing* concentric balanced flued Water Heaters are suitable for use on Natural Gas or LPG.

Note: * Models **LBF81** and **LBF121** are wall mounted units.

The heat exchanger comprises a welded steel tank with an enamel coating on its internal surface.

The flue ways are fitted with steel baffles for maximum heat transfer and the steel tank has foam injected insulation to minimise standby heat losses.

The stainless steel burners ensure maximum heat transfer to the water. Sacrificial magnesium anodes are fitted to offer protection from corrosion.

In-built features include automatic pilot ignition, flame failure protection, operating and high limit thermostats and a 100mm clean out access opening.

LBF Water Heaters are suitable for concentric balanced flue installation.

Correx[®] non sacrificial electrical anode protection, and flame failure indication are available from Lochinvar as ancillary options (refer to separate Ancillary Options List for details).

Full warranty terms and conditions are available at www.lochinvar.ltd.uk

Lochinvar Ltd reserves the right to change specifications without prior notice.
Issue 2 – February 2014

Model

LBF401

Lochinvar Ltd
7 Lombard Way | The MXL Centre
Banbury | Oxon | OX16 4TJ

Tel: +44 (0) 1295 269981
Fax: +44 (0) 1295 271640
Email: info@lochinvar.ltd.uk

www.lochinvar.ltd.uk

