

## EcoSword gas fired condensing water heaters

### Key features Include:

- On board controls
- Enamel lined storage vessel
- Factory fitted Correx

		<b>Model</b>
		<b>LGC 200-210 CE</b>
Nominal Input (net)	kW	11.0
Nominal Input (gross)	kW	12.1
Gas Flow Rate (natural gas)	m <sup>3</sup> /hr	1.15
Nominal Output	kW	11.9
<b>EFFICIENCY DATA-Building Regulations</b>		
Seasonal Efficiency (Part L2 Gross CV)	%	98.2
Maintenance Consumption value	MJ/M	252.3
<b>EFFICIENCY DATA-ErP and Energy Label</b>		
Ecodesign Energy Label rating		A
Water Heater efficiency	%	94
<b>GENERAL DATA</b>		
NOx emission @0% O <sub>2</sub>	mg/kWh	22
Recovery Rate @ 44°C	l/hr	239
Recovery Rate @ 50°C	l/hr	210
Recovery Rate @ 56°C	l/hr	188
Dimensions (height )	mm	1543
Dimensions (diameter)	mm	560
Dimensions (depth)	mm	760
Storage Capacity	litres	204
Weight (empty)	kg	106
Weight (full)	kg	310
Insulation Thickness	mm	50
Insulation Material		Polyurethane
Hot Outlet Connection (inches)	BSP (Female)	¾"
Cold Feed Connection (inches)	BSP (Female)	¾"
Gas Connection (mm)	CU (Male)	15
Condense Connection (mm)	OD (Female)	40
Electrical Requirements		230V /1Ph/ 50hz
Power Consumption	W	85
Sound Power Level	LWA(db)	41
Maximum Flue Gas Temperature	°C	42
Max Outlet Temperature	°C	85
Maximum Working Pressure	bar	8

**EcoSword water heaters** must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of [www.lochinvar.ltd.uk](http://www.lochinvar.ltd.uk)

Particular attention should be made to:-

- Dimensions and clearances page 38/80
- Vented and Unvented installation requirements page 39/40
- maintenance page 61

### **ErP and Warranty**

ErP Data including Product Fiche and Energy Labels where applicable and Warranty information are also available at [www.lochinvar.ltd.uk](http://www.lochinvar.ltd.uk)