

AMICUS LAHP-08HT ERP DATA TABLE

according regulations 813/2013

Model	LAHP-08HT		
Air to water heat pump	Yes		
Water to water heat pump	No		
Brine to water heat pump	No		
Low temperature heat pump	No		
Equipped with a supplementary heater	No		
Heat pump combination heater	No		
Parameters are declared for medium temperature applications	55°C		
Parameters are declared for average climate conditions			
Item	Symbol	Value	Unit
Rated heat output	P rated	18.6	[kW]
Tj = -7 [°C]	Pdh	16.5	[kW]
Tj = 2 [°C]	Pdh	10	[kW]
Tj = 7 [°C]	Pdh	6.47	[kW]
Tj = 12 [°C]	Pdh	2.88	[kW]
Tj = -20[°C] operational limit	Pdh	13.3	[kW]
Annual energy consumption	QHE	68.84	GJ
Bivalent temperature	Tbiv	-7	°C
Power consumption in modes other than active	Poff	0.02	[kW]
	Pto	0.02	[kW]
	Psb	0.02	[kW]
	Pck	0.08	[kW]
Capacity control	Variable		
Sound power level outdoors	Lwa	70	[dB(A)]
Emissions of nitrogen oxides	NOx	0	[mg/kWh]
Item	Symbol	Value	Unit
Seasonal space heating efficiency	ηs	115	[%]
Tj = -7 [°C]	COPd	1.89	[-]
Tj = 2 [°C]	COPd	2.97	[-]
Tj = 7 [°C]	COPd	3.87	[-]
Tj = 12 [°C]	COPd	4.61	[-]
Tj = -7 [°C]	COPd	1.89	[-]
Tj = -10 [°C]	COPd	1.69	[-]
Operating limit temperature	TOL	-16	[°C]
Cycling interval efficiency	COPcyc	3.75	[-]
Heating water operational limit	WTOL	65	[°C]
Supplementary heater rated output	Monovalent		
Rated airflow outdoors		8428	[m³/h]

1. according commission delegated regulation (EU) No 813/2013

ErP data table_LAHP-08HT_february2016



Lombard Way, The MXL Centre, Banbury, Oxon, OX16 4TJ

Tel: +44(0) 1295 269 981, Fax: +44(0) 1295 271 640, Email: info@lochinvar.ltd.uk

www.lochinvar.ltd.uk