

# AMICUS LAHP-702LT PRODUCT FICHE

According regulations 811/2013 and 812/2013

Model		LAHP-702LT	
Energy class	A++		
Air-to-water heat pump	Yes		
Low-temperature heat pump	Yes		
Supplementary heater	No		
Heat pump combination heater	No		
Item	Symbol	Value	Units of measurement
Rated heat output	Prated	43.53	[kW]
Tj = -7 [°C]	Pdh	38.51	[kW]
Tj = 2 [°C]	Pdh	32.08	[kW]
Tj = 7 [°C]	Pdh	38.92	[kW]
Tj = 12 [°C]	Pdh	43.77	[kW]
Tj = -7 [°C]	Pdh	38.51	[kW]
Tj = -9 [°C]	Pdh	36.03	[kW]
Tbivalent	Tbiv	-7	[°C]
Cycling interval capacity for heating	Pcych	-	[kW]
Degradation coefficient	Cdh	0.9309	[-]
Power consumption in off mode	Poff	0.02	[kW]
Power consumption in thermostat-off mode	Pto	0.2229	[kW]
Power consumption in standby mode	Psb	0.02	[kW]
Power consumption in crankcase heater mode	Pck	0.2	[kW]
Capacity control		Step	
Sound power level, indoor/outdoor measured	Lwa	0/77	[dB(A)]
Emissions of nitrogen oxides	NOx	0	[mg/kWh]
Seasonal space heating energy efficiency	ηs	158.400	[%]
Tj = -7 [°C]	COPd	2.513	[-]
Tj = 2 [°C]	COPd	4.187	[-]
Tj = 7 [°C]	COPd	5.848	[-]
Tj = 12 [°C]	COPd	7.021	[-]
Tj = -7 [°C]	COPd	2.513	[-]
Tj = -9 [°C]	COPd	2.316	[-]
Operation limit temperature	TOL	-16	[°C]
Cycling interval efficiency	COPcyc	-	[-]
Heating water operating limit temperature	WTOL	60	[°C]
Air flow rate		18043	[m³/h]
Heating energy demand		60947	[kWh]
Total electrical consumption		15103	[kWh]
SCOP		4.035	[-]
Climatic condition		Average	

ErP product fiche\_LAHP-702LT\_September 2019

