

LST166

Direct Storage Vessel

Lochinvar Ltd
8 Lombard Way
The MXL Centre, Banbury
Oxon, OX16 4TJ

+44 (0) 1295 269981
info@lochinvar.ltd.uk
www.lochinvar.ltd.uk

Key features Include:

- Clean out door
- Enamel lined storage vessel
- 5 year storage vessel warranty

RANGE

Storage Capacity	litres
------------------	--------

EFFICIENCY DATA-Part L2

Standing Loss	kWh/24hrs
Insulation Thickness	mm
Insulation Type	

EFFICIENCY DATA-ErP and Energy Label

Ecodesign Energy Label rating	
Standing Loss	w

GENERAL DATA

Recovery Rate @ 44°C	l/hr
Recovery Rate @ 50°C	l/hr
Recovery Rate @ 56°C	l/hr
Dimensions (height)	mm
Dimensions (diameter)	mm
Weight (empty)	kg
Weight (full)	kg
Minimum Working Pressure	bar
Maximum Working Pressure	bar
Hot Outlet / Cold Feed Connection (inches)	NPT
Flow Connection (inches)	NPT
Return Connection (inches)	NPT
Relief Valve Tapping (inches)	NPT
Immersion Bosses (inches)	

Model

LST166

685
2.98
75
Expanded foam
n/a
124
Use heat source data
Use heat source data
Use heat source data
1955
863
295
980
0.5
10.0
2
2½
2½
1
2¼

V1 06/2023