

TECHNICAL PRODUCT SUBMITTAL

Squire Indirect water heater

Model SIVS 66GE

Storage Capacity	litres	300
EFFICIENCY DATA-Part L2		
Insulation Thickness	mm	70
Insulation Type		Foliflex
Standing Loss	kWh/day	2.4
EFFICIENCY DATA-ErP and Energy Label		
EcoDesign Energy Label rating		C
Standing Loss	W	100
GENERAL DATA		
Max draw off capacity (first hour) at 50°C temperature rise	l/hr	1134
Heat-up Time at 50°C temperature rise	min	20
Dimensions (height)	mm	1375
Dimensions (diameter)	mm	740
Hot Outlet Connection (inches)	BSP	1½"
Cold Feed Connection (inches)	BSP	1½"
Coil Connection (inches)	BSP	1"
Weight (empty)	kg	103
Weight (full)	kg	403
Minimum Working Pressure	bar	0.5
Maximum Working Pressure	bar	10.0
COIL DATA		
Coil Rating (75/55°C)	kW	52
Coil Surface Area	m ²	2.45
Flow Rate (75/55°C)	l/sec	0.62
Pressure Loss	kPa	7.8
Maximum Coil Temperature	°C	110
Maximum Coil Pressure	bar	16

Squire Indirect water heaters must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of www.lochinvar.ltd.uk

Particular attention should be made to:-

- Dimensions and clearances
- Vented and Unvented installation requirements
- Maintenance

ErP and Warranty

ErP Data including Product Fiche and Energy Labels where applicable and Warranty information are also available at www.lochinvar.ltd.uk

TECHNICAL PRODUCT SUBMITTAL

Squire Indirect water heater

Legend	Description	Unit	Dimension
A	Total height	mm	1375
D	Diameter (with insulation)	mm	740
G	Coil outlet	mm	260
H	Coil inlet	mm	775
M	Cold water inlet	mm	70
N	Hot water outlet	mm	1320
P	Inspection opening	mm	330
R	Building return	mm	860
S	Sensor point	mm	500
T	T&P connection	mm	1030

Legend	Description	Unit	Size
1	Cold water inlet connection	BSP Inch	R 1½
2	Hot water outlet connection	BSP Inch	R 1½
3	Heat exchanger outlet	BSP Inch	Rp 1
4	Heat exchanger inlet	BSP Inch	Rp 1
5	Connection circulation	BSP Inch	Rp ¾
6	Diameter Inspection Opening	mm	115
7	Connection T&P	BSP Inch	Rp ¾
8	Connection Immersion well	BSP Inch	Rp ¾
10	Connection Anode	BSP Inch	Rp 1¼

