

TECHNICAL PRODUCT SUBMITTAL

LOK8-350

Heat Transfer Duty	kW	350
Thermal efficiency	%	99.5
Primary Side		
Inlet Temperature	°C	82
Outlet Temperature	°C	Varies Depending On Demand (43.3 At Full Demand)
Fluid Flow Rate	litre/second	2.2
Fluid type		Water
Connection size and type	Inch BSPT Female	1 1/4
Max Working Temperature	°C	99
Maximum Working Pressure	bar	10
Secondary Side		
Inlet Temperature	°C	Varies Depending On Demand (10 At Full Demand)
Outlet Temperature	°C	65
Fluid Flow Rate	litres/second	1.53
Fluid type		water
pressure drop	bar	0.20
Connection size and type	Inch BSPT Male	1 1/4
Max Working Temperature	°C	85
Maximum Working Pressure	bar	10
Performance		
Recovery Rate @ 55°C ΔT	litres/hour	5508
Recovery Rate @ 55°C ΔT	litres/second	1.53
Recovery Rate @ 50°C ΔT	litres/hour	6048
Recovery Rate @ 50°C ΔT	litres/second	1.68
Dimensions		
Height	mm	1445
Width	mm	643
Depth	mm	1023
Construction Details		
Number Of Plates		44
Plate Material		AISI 316 Stainless Steel
Gasket Material		EPDM - Clip On
Empty weight single head primary pump	kg	127
Empty weight twin head primary pump	kg	145
WRAS Approval Number		1401052

LOK packaged plate heat exchangers must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of www.lochinvar.ltd.uk

Particular attention should be made to:-

- Dimensions and clearances
- Vented and Unvented installation requirements
- maintenance

Warranty

Warranty information are also available at www.lochinvar.ltd.uk

TECHNICAL PRODUCT SUBMITTAL

LOK8-350

PORT	CONNECTION TYPE	FUNCTION
V1	1.25" BSPT FEMALE	BOILER IN
V4	1.25" BSPT FEMALE	BOILER OUT
F2	1.25" BSPT MALE	DHW IN
F3	1.25" BSPT MALE	DHW OUT

