

TECHNICAL PRODUCT SUBMITTAL

AMICUS LAHP-3504LTS AIR SOURCE HEAT PUMP

Heating Data ¹		
Heating Capacity (EN14511)	kW	339
Total Power input (EN14511)	kW	83.7
COP (EN14511)	W/W	4.05
Nominal flow rate	m ³ /h	59.56
Pressure drop across the heat pump	kPa	54.6
Design air flow rate	m ³ /h	112478
EcoDesign data ²		
Energy Label Rating Low temperature		A++
SCOP Low Temperature		3.91
Seasonal Efficiency Low temperature	%	153.5
Cooling Data (RV units only) ³		
Cooling Capacity (EN14511)	kW	287
Total Power input (EN14511)	kW	106
EER (EN14511)	W/W	2.71
Nominal flow rate	m ³ /h	49.14
Pressure drop across the heat pump	kPa	42.9
Design air flow rate	m ³ /h	115899
General		
Refrigerant type		R410A
Compressor Type		Scroll
Number of Compressors		4
Number of Circuits		2
Capacity steps		4
Minimum capacity step	%	25
Electrical Data		
Power supply	V/Ph/Hz	400/3+N/50
Maximum input power	kW	140
Maximum input current standard unit	A	246
Peak input current standard unit	A	490
Peak input current unit with soft start option fitted	A	366
Fuse rating (delayed)	A	400
Optional Hydraulic kit input power	kW	5.5
Optional Hydraulic kit maximum input current	A	10.4
Fans		
Fan type (standard unit)		Axial
Number of fans (standard unit)		6
Air flow rate for design	m ³ /h	115547
Sound power level ²	dB(A)	90
Sound pressure level ³	dB(A)	58

TECHNICAL PRODUCT SUBMITTAL

AMICUS LAHP-3504LTS AIR SOURCE HEAT PUMP



LAHP-3504LTS			Heating OUT						
Water Delivery Temperature			35C	40C	45C	50C	55C	59C	Max outlet
performance data	-10	Heat Output (KW)	180.0	176.0	174.0	N/A	N/A	N/A	45c
		Efficiency COP	2.1	1.9	1.7	N/A	N/A	N/A	
	-7	Heat Output (KW)	195.0	192.0	188.0	N/A	N/A	N/A	45c
		Efficiency COP	2.3	2.1	1.8	N/A	N/A	N/A	
	-5	Heat Output (KW)	206.0	202.0	198.0	193.0	N/A	N/A	50c
		Efficiency COP	2.4	2.2	1.9	1.7	N/A	N/A	
	-4	Heat Output (KW)	212.0	207.0	202.0	198.0	N/A	N/A	50c
		Efficiency COP	2.5	2.2	2.0	1.7	N/A	N/A	
	-3	Heat Output (KW)	217.0	214	211	208.0	N/A	N/A	50c
		Efficiency COP	2.5	2.28	2.05	1.8	N/A	N/A	
	-2	Heat Output (KW)	230.0	225.0	222.0	220.0	N/A	N/A	50c
		Efficiency COP	2.7	2.4	2.2	1.9	N/A	N/A	
	0	Heat Output (KW)	252.0	247.0	244.0	243.0	240.0	N/A	55c
		Efficiency COP	3.0	2.7	2.4	2.2	1.9	N/A	
	5	Heat Output (KW)	313.0	309.0	305.0	301.0	299.0	N/A	55c
		Efficiency COP	3.7	3.3	3.0	2.7	2.5	N/A	
	10	Heat Output (KW)	364.0	357.0	350.0	343.0	337.0	334.0	59c
		Efficiency COP	4.4	4.0	3.6	3.2	2.8	2.6	
15	Heat Output (KW)	405.0	397.0	387.0	378.0	371.0	366	59c	
	Efficiency COP	5.0	4.5	4.0	3.6	3.2	2.88		
20	Heat Output (KW)	444.0	434.0	423.0	412.0	402.0	398.0	59c	
	Efficiency COP	5.5	4.9	4.4	3.9	3.4	3.1		

Amicus air to water heat pumps must be installed and maintained in line with the Installation Commissioning and Maintenance Instructions which are available on the Literature & Downloads section of www.lochinvar.ltd.uk

TECHNICAL PRODUCT SUBMITTAL

AMICUS LAHP-3504LTS AIR SOURCE HEAT PUMP



Model	Octave band (Hz)								Lw		Lp
	63	125	250	500	1K	2K	4K	8K			
	dB	dB	dB	dB	dB	dB	dB	dB	Db	dB(A)	dB(A)
242	86.1	77.3	71.2	69.7	68.6	63.2	59.8	50.7	86.9	78	46
292	87.1	78.3	72.2	70.7	69.6	64.2	60.8	51.7	87.9	79	47
412	87.1	78.3	72.2	70.7	69.6	64.2	60.8	51.7	87.9	74	42
432	88.1	79.3	73.2	71.7	70.6	65.2	61.8	52.7	88.9	80	48
492	89.1	80.3	74.2	72.7	71.6	66.2	62.8	53.7	89.9	79	47
602	89.1	80.3	74.2	72.7	71.6	66.2	62.8	53.7	89.9	80	48
702	90.1	81.3	75.2	73.7	72.6	67.2	63.8	54.7	90.9	81	49
802	91.1	82.3	76.2	74.7	73.6	68.2	64.8	55.7	91.9	82	50
902	95.1	86.3	80.2	78.7	77.6	72.2	68.8	59.7	95.9	86	54
1002	96.1	87.3	81.2	79.7	78.6	73.2	69.8	60.7	96.9	87	55
1202	98.1	89.3	83.2	81.7	80.6	75.2	71.8	62.7	98.9	88	56
1402	99.1	90.3	84.2	82.7	81.6	76.2	72.8	63.7	99.9	89	58
1602	100.1	91.3	85.2	83.7	82.6	77.2	73.8	64.7	100.9	89	57
1802	100.1	91.3	85.2	83.7	82.6	77.2	73.8	64.7	100.9	90	58
2002	100.1	91.3	85.2	83.7	82.6	77.2	73.8	64.7	100.9	90	58
2302	102.1	93.3	87.2	85.7	84.6	79.2	75.8	66.7	102.9	92	60
2502	104.1	95.3	89.2	87.7	85.6	81.2	77.8	68.7	104.9	93	61
2504	101.1	92.3	86.2	84.7	83.6	78.2	74.8	65.7	101.9	91	59
3004	102.1	93.3	87.2	85.7	84.6	79.2	75.8	66.7	102.9	92	60
3204	103.1	94.3	88.2	86.7	85.6	80.2	76.8	67.7	103.9	92	60
3504	103.1	94.3	88.2	86.7	85.6	80.2	76.8	67.7	103.9	93	61
4004	103.1	94.3	88.2	86.7	85.6	80.2	76.8	67.7	103.9	94	64
4504	105.1	96.3	90.2	88.7	87.6	82.2	78.8	69.7	105.9	96	64
5004	105.1	96.3	90.2	88.7	87.6	82.2	78.8	69.7	105.9	94	62

Lw: sound power level according to ISO 3744

Lp: sound pressure level at 10mtrs from unit in free field conditions, direction factor Q=2 according to ISO 3744

TECHNICAL PRODUCT SUBMITTAL

AMICUS LAHP-3504LTS AIR SOURCE HEAT PUMP

