

EcoForce Gas Fired condensing water heaters

Key features include:

- Stainless steel heat exchanger
- On board controls
- 8 bar working pressure

Lochinvar Ltd
8 Lombard Way
The MXL Centre, Banbury
Oxon, OX16 4TJ

+44 (0) 1295 269981
info@lochinvar.ltd.uk

www.lochinvar.ltd.uk

EF+55/230

Nominal Input (net)	kW	52.9
Nominal Input (gross)	kW	58.8
Gas Flow Rate (natural gas)	m3/hr	1.48-5.40
Nominal Output (Gross)	kW	53.7
BUILDING REGULATIONS COMPLIANCE DATA		
Seasonal Efficiency (Part L2 Gross CV)	%	91.3
EFFICIENCY DATA-ErP and Energy Label		
Ecodesign Energy Label rating (Heater)		A
Water Heater efficiency	%	86.9
Ecodesign Energy Label rating (Vessel)		C
Standing Loss (Vessel)	W	78.8
GENERAL DATA		
NOx emission @0% O2	mg/kWh	29
Recovery Rate @ 44°C	l/hr	1050
Recovery Rate @ 50°C	l/hr	924
Recovery Rate @ 56°C	l/hr	825
Dimensions (Height)	mm	1550
Dimensions (Width)	mm	700
Dimensions (Depth)	mm	1000
Storage Capacity	litres	240
Weight (empty)	kg	117
Weight (full)	kg	357
Hot Outlet Connection (inches)	BSP	R 1½"
Cold Feed Connection (inches)	BSP	R 1½"
Gas Connection (inches)	BSP	R ¾"
Electrical Requirements		230V/1Ph/50hz
Power Consumption	W	195
Sound Power Level	LWA(db)	61
Max Outlet Temperature	°C	75
Minimum Working Pressure	bar	1.0
Maximum Working Pressure	bar	8.0